



12KW Heat Pump Water To Water Ground Source Heat Pump **Manufacturers**

Basic Information

. Place of Origin: China . Brand Name: meidibao CE · Certification:

M-D12WDH Model Number: • Minimum Order Quantity: 10 units

• Price: negotiate a price

Factory standard packing · Packaging Details:

• Delivery Time: 25-30 days

Payment Terms: T/T

. Supply Ability: 5 units one day



Product Specification

. Heat Exchanger: Plate Heat Exchanger

• Refrigerant: R410A

230V/1P/50HZ • Power Supply: Water To Water • Type:

EEV • Throttle Device:

LCD Touch Panel Standard/internet ,APP . Control:

Control Alternative

Name: **Custom Heat Pump**

. Highlight: 12KW Heat Pump Water To Water,

12KW Heat Pump Manufacturers,

12KW Ground Source Heat Pump Manufacturers

Product Description

12KW Custom Heat Pump inverter Ground Source Heat Pump Hot water+Room heating/cooling+Solar control

Product Description:

The water-to-water heat pump may be applied in a boiler/cooling tower setting, in a geothermal closed or open loop application, or in a hybrid application. All units accommodate service access to the controls, and other major components to contribute to greater serviceability and maintainability of the unit.

Water-to-water heat pumps transfer the underground heat energy from hot water or steam to indoor hot water or steam. This hot water or steam is then distributed within homes and businesses through radiators, hot water baseboard heaters, or radiant floor heating. When a hotter material comes into contact with a colder one, this temperature difference causes heat to naturally move from hot to cold, so heat pumps are renewable and efficient.

Feature:

- 1. High Cop: 5.10/5.25/5.20 (Rated working condition: heating: source side inlet/outlet water temp: 10/7, use side inlet/outlet water temp: 30/35)
- 2. Hot Water Temp: 20 to 65
- 3. Power Supply: 380V/50Hz/3P,220V/50Hz/1P
- 4. Source Side Temp: -3 to 30
- 5. Heating Capacity: 5KW/12KW/18KW/24KW

Specification:

Model		M-D12WDH
Performance at		
W10/7 ,W30/35		
Rated Heating	kW	12.5
Capacity		
Heating Capacity	kW	4.1-13.5
Range	<u> </u>	
COP	/	5.2
Rated Input Power	kW	2.4
Performance at W0/-		
3 ,W30/35		
Rated Heating	kW	11
Capacity		
Heating Capacity	kW	3.3-12.1
Range		
COP	7	4.47
Rated Input Power	kW	2.46
Functions	,	Hot water+Room heating/cooling+Solar control(Change over
	ľ	automatically)
Control	7	LCD touch panel standard/internet ,APP control alternative
Delivery Water		20-65
Power Supply	/	230V/1P/50Hz
Noise	dB(A	40
)	
Color	/	Optional/default white

Advantages:

Meidibao DC inverter water source heat pump utilize DC inverter technology and REPM compressor which running speeds can be adjusted follow the variation of ambient or water temperature, hence to regulate the output capacity with changeably, this can heat the storage tank or room much quicker than normal on/off heat pumps, and balance the water or air temp very precisely.

This also provides a very high COP as inverter system does not waste the energy. By inverter technology of frequency changeable the inverter heat pump can increase the compressor speeds to be more than 5000rpm at very low ambient at -25. This can increase refrigerant mass flow rate to offset the source energy loss in very cold climate and keep an acceptable performance



Meidibao Foshan Meidi Bao Electric Appliance Industry Co., Ltd

8613534489875

info@meidibao.com airsource-heatingpump.com

No9, Guangming North Road, Jiangyi, Leliu Town, Shunde District, Foshan City Guangdong Province, China