



# 30HP Commercial Air Source Water Heater Heat Pump For 6 System Heat **Pump Water Heater**

# **Basic Information**

. Place of Origin: China Brand Name: Meidibao CE · Certification:

Model Number: M-D105AAH

• Minimum Order Quantity: 2SET

• Price: negotiate a price · Packaging Details: Factory standards

• Delivery Time: Specific to the order based on regular

products 5 to 7 days. Custom made for 30

days

• Payment Terms: T/T

. Supply Ability: 5 SET one day



# **Product Specification**

• Use: Hot Water 0~43C Working Ambient

Temperature:

• Type: Air Source OEM . Service: 304 Material:

. Heat Exchanger: Shell In Coil

· Name: Commercial Air Source Heat Pump Highlight: 30HP Air Source Water Heater Heat Pump, Commercial Air Source Water Heater Heat Pump

## **Product Description**

#### 30HP Commercial Air Source Heat Pump for 6 system heat pump water heater

#### Product Description:

Meidibao air source heat pump system is powered by ambient air and operates around the clock: it provides continuous hot water thrughout the yeat and throughout the year,regardless of weather. The opreating cost is 67% less than that of gas water heater, 75% less than that of electric water heater and 60% less than that of boiler. Intelligent control: The unit is automatically controlled by a microcomputer, and automatically runs according to the water temperature of the water tank and the user's water use, without the need for special duty. Reasonable arrangement of low front

#### Feature

- 1. Compressor Choose the world famous brand rotary type or fully enclosed vortex compressor, low noise, low vibration, high efficiency, long service life. For units with multiple compressors inside, depending on the heat (cooling capacity), automatic unloading of the unit at partial load can be achieved to effectively save energy and at the same time avoid frequent start-up of the unit.
- 2. Water side heat exchanger The water side heat exchanger adopts high-efficiency shell tube heat exchanger or threaded casing heat exchanger, which has the characteristics of small volume, light weight, easy disassembly, convective heat conduction, high efficiency, and the maximum working pressure of 45kgf / cm2. The outside of the heat exchanger is insulated with 10mmPE to effectively prevent energy loss
- 3. Air side heat exchanger The air-side heat exchanger adopts an integral hydrophilic finned inner threaded tube design, with a large windward area, high heat transfer efficiency, resistance to oxidation and corrosion, and hydrophilic fins that are less prone to condensation and frosting, ensuring that the unit has sufficient heating capacity in the cold winter season, and that the unit can still operate normally for heating and defrosting even in low temperatures
- 4. Low noise fan he use of domestic famous brand motor, the use of axial impeller design, bearing is not easy to heat up, free of oil injection maintenance, blade more anti-aging, not deformed, the fan are strictly, static balance experiments, in order to obtain the best fan working point, fan efficiency and noise level.

## Specification:

Model:	M-D105AAH
Power supply:	380V~415V/3PH/50Hz
Working temperature:(°C)	-5~43
Min./Max hot water temperature:(°C)	55/60
Heating capacity output:	114 kw
Hot water flow:	2442L/h
Power input:	28.5 kw
Max Rated current:	65.4A
Compressor:	Scroll
Refrigerant:	R410A
Weight:	830kg
Dimension:(LxWxH)	2400*1050*2100mm

# Advantages:

Foshan Meidibao Electrical Appliance Co., Ltd. has been a manufacturer professionally specialized in research, development and production of Heat Pumps since 2005. Our well-equipped facilities and excellent quality control throughout all stages of production enables us to guarantee customer satisfaction

With a strong R&D center and production line, we are constantly specialized in producing and supplying air source heat pump, water/ground source heat pump, swimming pool heat pump, high temp. heat pump and EVI technology low temp. heat pump. All the products are developed and produced in the benchmark of CE, CCC,CQC certificates.











