



91kw High Efficiency Air Source Heat Pump For hospital / hotel / school

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 2units
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

Product Specification

 Material: 	Galvanized Sheet
• COP:	3.8~4.2
 Working Ambient Temperature: 	0~43C
 Power Supply: 	380V/3Ph/50Hz
• Function:	Commercial Heating System
• Fans:	Two
• Name:	Commercial Air Source Heat Pump
Highlight:	91kw High Efficiency Air Source Heat Pump, High Efficiency Hotel Air Source Heat Pump

China

CE

days T/T

Meidibao

KFXRS-84II-M3

negotiate a price

5 units one day

wooden frame or plywood box

Specific to the order based on regular products 5 to 7 days. Custom made for 30

91kw Commercial Air Source Heat Pump High Efficiency For hospital ,hotel,school

Product Description:

This commercial air source heat pump offers a sustainable and cost-effective heating option, providing a comfortable environment while also helping businesses manage their energy costs. It is a smart choice for those seeking an efficient and durable heating solution for their commercial properties.

Feature:

1. Compressor Choose the world famous brand rotary type or fully enclosed vortex compressor, low noise, low vibration, high efficiency, long service life . For units with multiple compressors inside, depending on the heat (cooling capacity), automatic unloading of the unit at partial load can be achieved to effectively save energy and at the same time avoid frequent start-up of the unit.

2. Timing,three period setting

- 3. Auto and manual defrosting function
- 4. Extensible electrical heater control function

Specification:

Product Name:	Air source heat pump	٦
Model:	KFXRS-84II-M3	
Climate type:	Normal	
Power supply	380V/3N/50Hz	
Rated heating capacity	91.2	
Rated power input	22.8KW	
Rated current	40.3A	
Refrigerant/charging volume	R410A/3200g*4	
Compressor brand/quantity	Copeland or panasonic / 4	
Rated hot water temperature:	55	
Max hot water temperature:	60	
Rated cold water temperature:	7	
water pipe size	DN65	
Noise level:	≤74dB(A)	
Anti-electric shock rate		
Protection grade:	IP×4	
Weight:	720KG	
Dimensions:	2000*1100*1960	
Manufacturing date:	See bar code	٦
Factory No.:	See bar code	
Test result:	Qualified	

Advantages:

Heat pump form heating: no need to build a boiler room, directly from the air heat absorption, reduce the cost, clean and safety, avoid environmental pollution; For some winter by heat pump heat shortage places, it can also choose auxiliary electric heating to meet the heat requirements. High efficiency, energy saving, reliable performance: choose the world famous brand rotary type or fully enclosed vortex compressor and the world famous brand high-quality refrigeration components, to ensure that the whole machine plays the highest energy efficiency. The multi-system unit adopts a two-stage energy regulation system, which is especially suitable for partial load, more energy saving and can effectively protect the frequent start of the system.







No9, Guangming North Road, Jiangyi, Leliu Town, Shunde District, Foshan City Guangdong Province, China