



40HP Swimming Pool Air Source Heat Pump 304 Sheet Metal 304 Shell **Titanium Tube**

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- · Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Name:
- Heat Exchanger:
- Refrigerant:
- Power Supply:
- Type:
- Brand Name:
- Place Of Origin:
- Highlight:

Swimming Pool Air Source Heat Pump

304 Shell Titanium Tube

- R410A
- 380V/3PH/60Hz Or 50Hz
- - MEIDIBAO

China

CE

1unit

T/T

meidibao

M-D168AAS

25-30 days

negotiate a price Factory standards

5 units one day

- China

Air Source Heat Pump

- 40HP Swimming Pool Air Source Heat Pump, 304 Shell Titanium Pool Heat Pump

40HP Swimming Pool Air Source Heat Pump 304 sheet metal 304 shell titanium tube

Product Description:

Meidibao air source heat pump system is powered by ambient air and operates around the clock: it provides continuous hot water thrughout the yeat and throughout the year, regardless of weather . The opreating cost is 67% less than that of gas water heater, 75% less than that of electric water heater and 60% less than that of boiler. Intelligent control: The unit is automatically controlled by a microcomputer, and automatically runs according to the water temperature of the water tank and the user's water use, without the need for special duty. Reasonable arrangement of low front

Feature:

1. Foshan Meidibao Electrical Appliance Co.,Ltd. has been a manufacturer professionally specialized in research, development and production of Heat Pumps since 2005. Our well-equipped facilities and excellent quality control throughout all stages of production enables us to guarantee customer satisfaction.

- 2. can OEM ODM ,Experienced
- 3. 304 shell titanium tube heat exchanger
- 4. 304# sheet metal
- 5. Strong corrosion resistance

Specification:

Product	Air source heat pump
Model	M-D168AAS
Climatic type	Normal
Power supply	380V /60Hz
Rated heating capacity(A24 /W26)	168kW
Rated power input	36.5kW
Max Rated current	83.7A
Refrigerant	R410
working temp	0-43
water pipe size	3"
Noise	≤78dB(A)
Product dimension	2200×2000×2300mm
Net weight	1020kg
Testing condition:ambient Dry/Wet Bulb Temp: 20 / 15	;Water Inlet Outlet Temp: 15 / 55

Advantages:

Heat pump form heating: no need to build a boiler room, directly from the air heat absorption, reduce the cost, clean and safety, avoid environmental pollution; For some winter by heat pump heat shortage places, it can also choose auxiliary electric heating to meet the heat requirements. High efficiency, energy saving, reliable performance: choose the world famous brand rotary type or fully enclosed vortex compressor and the world famous brand high-quality refrigeration components, to ensure that the whole machine plays the highest energy efficiency. The multi-system unit adopts a two-stage energy regulation system, which is especially suitable for partial load, more energy saving and can effectively protect the frequent start of the system.





