



10kw Air Source Heat Pump , Side Discharge Heat Pump High Efficiency Shell In Tube

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meidibao
- Certification: CE
- Model Number: KFXRS-10I-M1C
- Minimum Order Quantity: 6 units
- Price: negotiate a price
- Packaging Details: Factory standards
- Delivery Time: Specific to the order based on regular products 5 to 7 days. Custom made for 30 days
- Payment Terms: T/T
- Supply Ability: 30 units one day



Product Specification

- Name: High Efficiency Air Source Heat Pump 10kw
- Material: Galvanized Sheet
- Heat Exchanger: Shell In Coil
- Use: Hair Salon, Villa, Apartment
- COP: 4
- Working Ambient Temperature: 0~43C
- Heating: 10KW
- Highlight: **10kw Air Source Heat Pump,
High Efficiency Air Source Heat Pump 10kw,
Side Discharge Heat Pump High Efficiency**

Product Description

10KW side discharge Commercial Air Source Heat Pump high efficiency shell in tube

Product Description:

One of the key features of this heat pump is its remarkable energy efficiency. It utilizes advanced technology to extract heat from the outside air during the heating mode and transfer it indoors, significantly reducing energy consumption compared to traditional heating systems.

The commercial-grade construction ensures durability and reliability, capable of withstanding heavy usage and demanding operating conditions. It is built with high-quality materials and components that are designed to last.

The intelligent control system offers precise temperature control and customizable settings to meet the specific needs of different commercial environments. It may include features such as programmable schedules, energy monitoring, and remote access for easy management and optimization of energy usage.

Feature:

1. Side Discharge Design
2. Energy Efficiency
3. All-Weather Performance
4. Low noise

Specification:

Product	10KW side-out air source heat pump
Model	KFXRS-10I-M1C
working temp	0 ~43
Power supply	220V /50Hz
Rated heating capacity	10kW
Rated power input	2.5kW
Rated current	11.3A
Max current	14.7A
Hot water flow	215L/h
Refrigerant/Charge	R410/1600g
Max exhaust working pressure	3.0MPa
Min suction working pressure	0.05MPa
set temp. range	20 ~60
water pipe size	DN25
Noise	≤65dB(A)
Anti-electric shock rate	I
Protection grade	IP×4
Testing condition:ambient Dry/Wet Bulb temp:20 /15 ,Water Inlet Outlet temp:15 /55	

Advantages:

Heat pump form heating: no need to build a boiler room, directly from the air heat absorption, reduce the cost, clean and safety, avoid environmental pollution; For some winter by heat pump heat shortage places, it can also choose auxiliary electric heating to meet the heat requirements. High efficiency, energy saving, reliable performance: choose the world famous brand rotary type or fully enclosed vortex compressor and the world famous brand high-quality refrigeration components, to ensure that the whole machine plays the highest energy efficiency. The multi-system unit adopts a two-stage energy regulation system, which is especially suitable for partial load, more energy saving and can effectively protect the frequent start of the system.







Meidibao® Foshan Meidi Bao Electric Appliance Industry Co., Ltd



8613534489875



info@meidibao.com



airsource-heatingpump.com

No9, Guangming North Road, Jiangyi, Leliu Town, Shunde District, Foshan City Guangdong Province, China