



## 8KW Monoblock Design Easy Installation Air Source Heat Pump R22 Refrigerant

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Meidibao
- Certification: CE
- Model Number: KF115-MS02I
- Minimum Order Quantity: 10SET
- Price: negotiate a price
- Packaging Details: Cartons and wooden pallets
- Delivery Time: Specific to the order based on regular products 5 to 7 days. Custom made for 30 days
- Payment Terms: T/T
- Supply Ability: 30 SET one day



### Product Specification

- Working Ambient Temperature: 0~43C
- Heat Exchanger: Tube In Tube
- Material: Galvanized Sheet
- Use: Hot Water
- COP: 3.8~4.2
- Water Pump: Included
- Name: Monoblock Heat Pump
- Highlight: **R22 Refrigerant Monoblock Heat Pump ,  
8KW Monoblock Heat Pump,  
Easy Installation Monoblock Heat Pump**

for more products please visit us on [airsource-heatingpump.com](http://airsource-heatingpump.com)

## Product Description

### 8KW Monoblock Design Easy Installation Air Source Heat Pump R22 Refrigerant

#### Product Description:

The **8KW Monoblock Air Source Heat Pump** is a high-performance and energy-efficient heating solution, designed for **residential and light commercial applications**. With its **compact design** and **easy installation**, this heat pump provides **reliable heating and hot water** while minimizing energy consumption.

#### Feature:

1. Monoblock Design
2. High Efficiency
3. Eco-Friendly Refrigerant (R22)
4. Quiet Operation
5. Durable & Weather-Resistant

#### Specification:

Product	Air source heat pump	Air source heat pump
Model	KF115-MS02I	KFXRS-9I-M2C
Climatic type	Normal	Normal
Power supply	220V /50Hz	220V /50Hz
Rated heating capacity	4.9kW	8.05kW
Rated power input	1.29kW	2.36kW
Max Rated current	7.6A	13.6A
Refrigerant / Charge	R410/1050	R410/1100
Rated water temp.	55	55
Max hot water temp.	60	60
working temp	0-43	0-43
water pipe size	DN20	DN20
Noise	≤60dB(A)	≤65dB(A)
Product dimension	800×290×800mm	800×290×800mm
Net weight	53kg	63kg
Testing condition: ambient Dry/Wet Bulb Temp: 20 / 15 ;Water Inlet/Outlet Temp: 15 / 55		

#### Advantages:

1. Easy Installation & Space-Saving
2. High Energy Efficiency & Cost Savings
3. Reliable Performance in Various Climates
4. Eco-Friendly Heating Solution
5. Low Noise Operation
6. Smart & User-Friendly Control



No9, Guangming North Road, Jiangyi, Leliu Town, Shunde District, Foshan City Guangdong Province, China