



# R32 Air Source Heat Pump Commercial Heat Pumps Water Heater 2 Row **Evaporator**

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 3 units
- Price:
- Packaging Details: Factory standards
- Delivery Time:
- Specific to the order based on regular products 5 to 7 days. Custom made for 30 days T/T • Payment Terms: • Supply Ability: 30 units one day

negotiate a price

KFXKS-53II-M2(LRS)

China

CE

Meidibao



### **Product Specification**

• Name:	Commercial Cooling And Heating Heat Pump
<ul> <li>Evaporator Color:</li> </ul>	Gold Or Blue
<ul> <li>Throttling Device:</li> </ul>	EEV
Refrigerant:	R410A
Cooling:	32.2KW
<ul> <li>Heating:</li> </ul>	48.5KW
<ul> <li>Heat Exchanger:</li> </ul>	Titanium Shell In Tube
• Highlight:	Commercial Heat Pumps Water Heater, R32 Air Source Heat Pump

### Meidibao R32 Air Source Heat Pump Commercial Heat Pumps Water Heater 2 Row Evaporator

#### **Product Description:**

The Meidibao R32 Commercial Air Source Heat Pump is designed for efficient water heating in large-scale applications, offering reliable performance and low energy consumption. Equipped with an advanced 2-row evaporator, it ensures faster heat exchange, improving overall efficiency and stability. With R32 refrigerant, it delivers eco-friendly heating while reducing the environmental impact. Ideal for hotels, resorts, gyms, and industrial water heating needs, this heat pump offers year-round reliability.

#### Feature:

R32 Eco-Friendly Refrigerant 2-Row Evaporator Design Energy-Saving Operation Smart Control System Durable Construction Low Noise and Stable Performance Why Choose Meidibao?

High-performance industrial heat pump with durable heat exchanger Energy-efficient and eco-friendly heating solution Long-lasting design for industrial and commercial applications Cost-effective alternative to traditional heating systems

#### **Specifications:**

Power supply: 380V/3PH/50Hz Refrigerant: R32 (eco-friendly and efficient) Heating capacity: 20kW – 100kW (various models available) Evaporator: 2-row design for enhanced heat exchange Water temperature range: 15°C – 60°C Compressor: Copeland / Panasonic / Mitsubishi (high-efficiency and durable) Noise level: ≤55 dB(A) Control system: Digital display with WiFi remote control

Specification:

opeenieutern	
Heating And Cooling Heat Pump	
KFXKS-53II-M2(LRS)	
Normal	
380V /50Hz	
48.5kW	
13.1kW	
32.2KW	
14.6kW	
35.5A	
R410/3600g×2	
55	
7	
60	
0-43	
DN40	
≤68dB(A)	
1500×760×1120mm	
320kg	

### Sample Project :





Meidikao<sup>®</sup> Foshan Meidi Bao Electric Appliance Industry Co., Ltd

S 8613534489875 S info@meidibao.com Airsource-heatingpump.com

No9, Guangming North Road, Jiangyi, Leliu Town, Shunde District, Foshan City Guangdong Province, China